

Electrical Specifications

Voltage: Duty Cycle: Resistance: 6 VDC Continuous

9.5 ohms ± 10% (@ 20c)

Amps @ rated Volts: 0.83 Watts @ rated Volts: 5.0

Holding: 44 lbs (1/4" Thick 1215 CRS @ 20c)


-40c to 60c (range) Operating Temp:

Additional Components

10-32 x 13/16" Long (Hex Socket Head Cap) w/Nylok Screw:

Spring: N/A Spiral Pin: N/A Potting: N/A

Housing - Zinc or Electroless Nickel Plating (0.0002-0.0003") Finish:



		1		1			<u> </u>			
			UNLESS OTHERWISE SPECIFIED:		NAME	DATE	۸ D			
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF			DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±.015 ANGULAR: MACH±2 BEND±2 TWO PLACE DECIMAL ±.005 THREE PLACE DECIMAL ±.003 INTERPRET GEOMETRIC	DRAWN	K.H.	07.20.11	APW COMPANY			T
				CHECKED	J.K.	07.20.11	TITLE:			
				ENG APPR.	J.K.	07.20.11	_	P/N: EM137-6-2		
				MFG APPR.	J.K.	07.20.11	P/			
	1			Q.A.						
			TOLERANCING PER: ANSI	COMMENTS:						
			MATERIAL				SIZE DWG.	NO.		REV
							Λ	E171		
	NEXT ASSY	USED ON	FINISH				$ \mathbf{A} $	5474		
APW COMPANY IS PROHIBITED.	APPLICATION		DO NOT SCALE DRAWING				SCALE: 1:1	WEIGHT:	SHEE	T 1 OF 1
Α.										