

## **Electrical Specifications**

Voltage: Duty Cycle: 24 VAC Continuous

Resistance: 165 ohms ± 10% (@ 20c)

Amps @ rated Volts: 0.21 Watts @ rated Volts: 5.0

33 lbs (1/4" Thick 1215 CRS @ 20c) -40c to 60c (range) Holding:

Operating Temp:


## **Additional Components**

Screw: 10-32 x 13/16" Long (Hex Socket Head Cap) w/Nylok

Spring: N/A Spiral Pin: N/A Potting: N/A

Housing - Zinc or Electroless Nickel Plating (0.0002-0.0003") Finish:

5



 $\emptyset$  1.38

Center Post Recessed

.81

Ø.318

.66

(.003 - .005)

Quick Release

				UNLESS OTHERWISE SPECIFIED:		NAME	DATE				) A K I	\/
				DIMENSIONS ARE IN INCHES	DRAWN	K.H.	07.20.11	APW COMPAN				Y
				TOLERANCES: FRACTIONAL±.015 ANGULAR: MACH±2 BEND±2 TWO PLACE DECIMAL ±.005 THREE PLACE DECIMAL ±.003	CHECKED	J.K.	07.20.11	TITLE:				
					ENG APPR.	J.K.	07.20.11		D /N I		ac-122	
					MFG APPR.	J.K.	07.20.11		P/N	: EM137-24a		
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS PROHIBITED.			INTERPRET GEOMETRIC TOLERANCING PER: ANSI	Q.A.							
					COMMENTS:	OMMENTS:						
				MATERIAL					DWG.	NO.		REV
								Λ.		5477		
		NEXT ASSY	USED ON	FINISH				A				
		APPLICATION		DO NOT SCALE DRAWING				SCA	LE: 1:1	WEIGHT:	SHEE	T 1 OF 1

3