Electrical Specifications

Voltage: 115 VAC Duty Cycle: Continuous

Resistance: 652 ohms ± 10% (@ 20c)

Amps @ rated Volts: 0.13 Watts @ rated Volts: 15.0

Holding: 300 lbs (1/4" Thick 1215 CRS @ 20c) -40c to 60c (range)

Operating Temp:

Additional Components

5/16-18 x 1 1/2" Long (Socket Head Cap Screw) w/Nylok Screw:

Spring: Spiral Pin: N/A


Potting: United Resin Corp. (El-cast Black)

Housing - Zinc or Electroless Nickel Plating Finish:


(0.0002-0.0003")

Center Post Recessed (.003 - .005)**Quick Release** - Ø.49 Ø3.00 1.50 .40

8" from coil to rectifier 11" after 18 Ga. Type 1015 UL



 \emptyset .32 THRU ALL $3/8-16 \ UNC - 2B \ \overline{\lor} \ 1.13$ √ Ø .38 X 45°, NEAR SIDE



		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	Ī
		DIMENSIONS ARE IN INCHES	DRAWN	K.H.	07.15.11	
			CHECKED	J.K.	07.15.11	T
		ANGULAR: MACH±2 BEND±2 TWO PLACE DECIMAL ± .005 THREE PLACE DECIMAL ± .003	ENG APPR.	J.K.	07.15.11	
			MFG APPR.	J.K.	07.15.11	
		INTERPRET GEOMETRIC	Q.A.			l
PROPRIETARY AND CONFIDENTIAL		FOLERANCING PER: ANSI	COMMENTS:		-	
INFORMATION CONTAINED IN THIS		MATERIAI			,	П

USED ON

FINISH

APW COMPANY

TITLE:

P/N: EM300-115ac-112

SIZE	DWG.	5547		REV
SCALE: 1:2		WEIGHT:	SHEET 1 OF 1	

5

DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION

IN PART OR AS A WHOLE WITHOUT THE

WRITTEN PERMISSION OF APW COMPANY IS PROHIBITED.

APPLICATION

NEXT ASSY

3

DO NOT SCALE DRAWING