



Electrical Specifications

Voltage: 24 VDC
Duty Cycle: Continuous
Resistance: 165 ohms \pm 10% (@ 20c)
Amps @ rated Volts: 0.21
Watts @ rated Volts: 5.0
Holding: 33 lbs (1/4" Thick 1215 CRS @ 20c)
Operating Temp: -40c to 60c (range)

Additional Components

Screw: 91-765-1 (#8-32 x .83" standoff)
Spring: LC-022D-01 M
Spiral Pin: N/A
Potting: N/A

Finish: Housing - Zinc or Electroless Nickel Plating
(0.0002-0.0003")

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE
		DIMENSIONS ARE IN INCHES	DRAWN	K.H.	07.20.11
		TOLERANCES:	CHECKED	J.K.	07.20.11
		FRACTIONAL \pm .015	ENG APPR.	J.K.	07.20.11
		ANGULAR: MACH \pm 2 BEND \pm 2	MFG APPR.	J.K.	07.20.11
		TWO PLACE DECIMAL \pm .005	Q.A.		
		THREE PLACE DECIMAL \pm .003	COMMENTS:		
		INTERPRET GEOMETRIC TOLERANCING PER: ANSI			
		MATERIAL			
NEXT ASSY	USED ON	FINISH			
APPLICATION		DO NOT SCALE DRAWING			

APW COMPANY INC.

TITLE:
EM137-24-121-D

SIZE A	DWG. NO. 6125	REV
------------------	-------------------------	-----

SCALE: 1:1	WEIGHT:	SHEET 1 OF 1
------------	---------	--------------