



Electrical Specifications

Voltage: 24 VDC
Duty Cycle: Continuous
Resistance: 52.4 ohms \pm 10% (@ 20c)
Amps @ rated Volts: 0.458
Watts @ rated Volts: 11
Holding: 350 lbs (1/4" Thick 1215 CRS @ 20c)
Operating Temp: -40c to 60c (range)
Lead Wire: Cable, Flexible, 2 X 20AWG

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.

Client	Client P/N	UNLESS OTHERWISE SPECIFIED:	NAME	DATE	APW COMPANY	
		DIMENSIONS ARE IN MILLIMETERS TOLERANCES: FRACTIONAL \pm .25 ANGULAR: MACH \pm BEND \pm TWO PLACE DECIMAL \pm .25 THREE PLACE DECIMAL \pm .15	DRAWN	D.P.	6.21.23	TITLE:
		Break Sharp edges 0.002" unless otherwise noted	CHECKED			Rectangle Electromagnet 150mm
		MATERIAL	ENG APPR.			EMR-4035-150-24
		FINISH	MFG APPR.			SIZE DWG. NO. REV
NEXT ASSY	USED ON		Q.A.			A 7008
APPLICATION		DO NOT SCALE DRAWING	COMMENTS:		SCALE: 1.75	WEIGHT: SHEET 1 OF 1