



Electrical Specifications

Voltage: 24 VDC
Duty Cycle: Continuous
Resistance: 44.3 ohms \pm 10% (@ 20c)
Amps @ rated Volts: 0.542
Watts @ rated Volts: 13
Holding: 500 lbs (1/4" Thick 1215 CRS @ 20c)
Operating Temp: -40c to 60c (range)
Lead Wire: Cable, Flexible, 2 X 20AWG

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.

| Client | Client P/N | UNLESS OTHERWISE SPECIFIED: | NAME | DATE | APW COMPANY | |
|-------------|------------|---|-----------|------|-------------|----------------------------------|
| | | DIMENSIONS ARE IN MILLIMETERS | DRAWN | D.P. | 6.21.23 | TITLE: |
| | | TOLERANCES: | CHECKED | | | Rectangle Electromagnet 200mm |
| | | FRACTIONAL \pm .25 | ENG APPR. | | | EMR-4035-200-24 |
| | | ANGULAR: MACH \pm BEND \pm | MFG APPR. | | | SIZE DWG. NO. REV |
| | | TWO PLACE DECIMAL \pm .25 | Q.A. | | | A 7009 |
| | | THREE PLACE DECIMAL \pm .15 | COMMENTS: | | | SCALE: 1.75 WEIGHT: SHEET 1 OF 1 |
| | | Break Sharp edges 0.002" unless otherwise noted | | | | |
| | | MATERIAL | | | | |
| NEXT ASSY | USED ON | FINISH | | | | |
| APPLICATION | | DO NOT SCALE DRAWING | | | | |