



**Electrical Specifications**

- Voltage:** 24 VDC
- Duty Cycle:** Continuous
- Resistance:** 30.3 ohms ± 10% (@ 20c)
- Amps @ rated Volts:** 0.792
- Watts @ rated Volts:** 19
- Holding:** 860 lbs (1/4" Thick 1215 CRS @ 20c)
- Operating Temp:** -40c to 60c (range)
- Lead Wire:** Cable, Flexible, 2 X 20AWG

2X M8x1.0 Tapped Hole

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.

|             |                      |  |           |      |                                       |
|-------------|----------------------|--|-----------|------|---------------------------------------|
| Client      | Client P/N           | UNLESS OTHERWISE SPECIFIED:<br>DIMENSIONS ARE IN MILLIMETERS<br>TOLERANCES:<br>FRACTIONAL ± .25<br>ANGULAR: MACH ±    BEND ±<br>TWO PLACE DECIMAL ±.25<br>THREE PLACE DECIMAL ±.15 | NAME      | DATE | <b>APW COMPANY</b>                    |
|             |                      |  | DRAWN     | D.P. |                                       |
| NEXT ASSY   | USED ON              | MATERIAL   | CHECKED   |      | TITLE:                                |
|             |                      |  | ENG APPR. |      | Rectangle Electromagnet 300mm         |
| APPLICATION | DO NOT SCALE DRAWING | FINISH   | MFG APPR. |      | EMR-4035-300-24                       |
|             |                      |  | Q.A.      |      | SIZE DWG. NO. REV                     |
|             |                      |  | COMMENTS: |      | <b>A</b> <b>7010</b> 1                |
|             |                      |  |           |      | SCALE: 1:2    WEIGHT:    SHEET 1 OF 1 |