







Electrical Specifications

Voltage: Duty Cycle: 24 VDC 10%

3.3 lbs (1/4" Thick 1215 CRS @ 20c) -40c to 60c (range)

Resistance: 95 ohms ± 10% (@ 20c)
Amps @ rated Volts: 0.25
Watts @ rated Volts: 6.06
Holding: 3.3 lbs (1/4" Thick 1215 (0.25)
Lead Wire Positive: Lead Wire Negative: Prown

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICLY PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE		ΛD		$D\Lambda\Lambda$	IV	
DIMENSIONS ARE IN MM TWO PLACE DECIMAL ±.25 THREE PLACE DECIMAL ±.13	DRAWN	DP	9.27.23	APW COMPANY					
	CHECKED			TITLE:					
	ENG APPR.			EML12mm-24					
	MFG APPR.								
Break Sharp edges 0.05 unles otherwise noted	Q.A.								
	COMMENTS:								
MATERIAL				SIZE	DWG.			REV	
FINISH				A		6663			
DO NOT SCALE DRAWING	-			SCAI	LE: 2:1	WEIGHT:	SHEE	T 1 OF 1	
3			2			1			

5 3