



### Electrical Specifications

- Voltage:** 12 VDC
- Duty Cycle:** 10%
- Resistance:** 5.3 ohms  $\pm$  10% (@ 20c)
- Amps @ rated Volts:** 2.26
- Watts @ rated Volts:** 27.17
- Holding:** 44.9 lbs (1/4" Thick 1215 CRS @ 20c)
- Operating Temp:** -40c to 60c (range)
- Lead Wire Positive:** Red
- Lead Wire Negative:** Blue

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>APW COMPANY</b>	
DIMENSIONS ARE IN MM		DRAWN	DP		
TWO PLACE DECIMAL $\pm$ .25		CHECKED			TITLE: <b>EML35mm-12</b>
THREE PLACE DECIMAL $\pm$ .13		ENG APPR.			
Break Sharp edges 0.05 unless otherwise noted		MFG APPR.			
MATERIAL		Q.A.			
FINISH		COMMENTS:			SIZE
DO NOT SCALE DRAWING					DWG. NO.
					<b>A</b>
					<b>6668</b>
					REV
					SCALE: 1:1
					WEIGHT:
					SHEET 1 OF 1

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.