



### Electrical Specifications

- Voltage:** 12 VDC
- Duty Cycle:** 10%
- Resistance:** 40 ohms  $\pm$  10% (@ 20c)
- Amps @ rated Volts:** 0.3
- Watts @ rated Volts:** 3.6
- Holding:** 4.49 lbs (1/4" Thick 1215 CRS @ 20c)
- Operating Temp:** -40c to 60c (range)
- Lead Wire Positive:** Red
- Lead Wire Negative:** Blue

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>APW COMPANY</b>			
DIMENSIONS ARE IN MM		DRAWN	DP			9.27.23	
TWO PLACE DECIMAL $\pm$ .25		CHECKED			TITLE: <b>EML15mm-12</b>		
THREE PLACE DECIMAL $\pm$ .13		ENG APPR.					
Break Sharp edges 0.05 unless otherwise noted		MFG APPR.					
MATERIAL		Q.A.					
FINISH		COMMENTS:			SIZE	DWG. NO.	REV
DO NOT SCALE DRAWING					<b>A</b>	<b>6674</b>	
		SCALE: 2:1		WEIGHT:	SHEET 1 OF 1		

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.