



**Electrical Specifications**

- Voltage:** 24 VDC
- Duty Cycle:** 10%
- Resistance:** 38.9 ohms ± 10% (@ 20c)
- Amps @ rated Volts:** 0.62
- Watts @ rated Volts:** 14.81
- Holding:** 40 lbs (1/4" Thick 1215 CRS @ 20c)
- Operating Temp:** -40c to 60c (range)
- Lead Wire Positive:** Red
- Lead Wire Negative:** Brown

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>APW COMPANY</b>			
DIMENSIONS ARE IN MM		DRAWN	DP			9.27.23	
TWO PLACE DECIMAL ±.25		CHECKED			TITLE: <b>EML32mm-24</b>		
THREE PLACE DECIMAL ±.13		ENG APPR.					
Break Sharp edges 0.05 unless otherwise noted		MFG APPR.					
MATERIAL		Q.A.					
FINISH		COMMENTS:			SIZE	DWG. NO.	REV
DO NOT SCALE DRAWING					<b>A</b>	<b>6678</b>	
		SCALE: 1:1		WEIGHT:	SHEET 1 OF 1		

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.