


## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICLY PROHIBITED.

5



## **Electrical Specifications**

Voltage: Duty Cycle: 24 VDC 10%

Resistance: 20.5 ohms ± 10% (@ 20c)

Amps @ rated Volts: 1.17
Watts @ rated Volts: 28.1
Holding: 44.9

44.9 lbs (1/4" Thick 1215 CRS @ 20c) -40c to 60c (range)

Operating Temp: Lead Wire Positive:

Red Lead Wire Negative: Brown

3

UNLESS OTHERWISE SPECIFIED:		NAME	DATE		۸D۱		ΣΛΝ	V
DIMENSIONS ARE IN MM  TWO PLACE DECIMAL ±.25 THREE PLACE DECIMAL ±.13	DRAWN	DP	9.27.23	APW COMPANY				
	CHECKED			TITLE:				
	ENG APPR.			EML35mm-24				
	MFG APPR.							
Break Sharp edges 0.05 unles otherwise noted	Q.A.							
	COMMENTS:							
MATERIAL				SIZE DWG. NO. REV			REV	
FINISH	-			Α		6679		
DO NOT SCALE DRAWING				SCAL	E: 1:1	WEIGHT:	SHEE	T 1 OF 1

2