



$\phi .21 \nabla .68$   
1/4-28 UNF - 2B  $\nabla .50$

### Electrical Specifications

**Voltage:** 24 VDC  
**Duty Cycle:** Continuous  
**Resistance:** 140 ohms  $\pm 10\%$  (@ 20c)  
**Amps @ rated Volts:** 0.17  
**Watts @ rated Volts:** 4.0  
**Holding:** 25 lbs (1/4" Thick 1215 CRS @ 20c)  
**Operating Temp:** -40c to 60c (range)

### Additional Components

**Screw:** N/A  
**Spring:** N/A  
**Spiral Pin:** N/A  
**Potting:** United Resin Corp. (El-cast Black)

**Finish:** Housing - Zinc or Electroless Nickel Plating (0.0002-0.0003")

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>APW COMPANY</b>	
		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm .010$ ANGULAR: MACH $\pm$ BEND $\pm$ TWO PLACE DECIMAL $\pm .005$ THREE PLACE DECIMAL $\pm .003$		DRAWN	D.P.		
		Break Sharp edges 0.002" unless otherwise noted		CHECKED		TITLE:	
		MATERIAL		ENG APPR.		P/N: EM100-24-212-A	
		FINISH		MFG APPR.		SIZE DWG. NO. REV	
NEXT ASSY	USED ON			Q.A.		A 7022	
APPLICATION		DO NOT SCALE DRAWING		COMMENTS:		SCALE: 3:2 WEIGHT: SHEET 1 OF 1	