



### Electrical Specifications

**Voltage:** 24 VDC  
**Duty Cycle:** 10%  
**Resistance:** 55.9 ohms  $\pm$  10% (@ 20c)  
**Amps @ rated Volts:** 0.43  
**Watts @ rated Volts:** 10.3  
**Holding:** 112 lbs (1/4" Thick 1215 CRS @ 20c)  
**Operating Temp:** -40c to 60c (range)  
**Lead Wire Positive:** Red  
**Lead Wire Negative:** Brown

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	APW COMPANY	
DIMENSIONS ARE IN MM		DRAWN	DP	9.27.23	TITLE:
TWO PLACE DECIMAL $\pm$ .25		CHECKED			EML50mm-24
THREE PLACE DECIMAL $\pm$ .13		ENG APPR.			
Break Sharp edges 0.05 unless otherwise noted		MFG APPR.			SIZE
MATERIAL		Q.A.			DWG. NO.
FINISH		COMMENTS:			6681
DO NOT SCALE DRAWING					REV
				SCALE: 1:1	WEIGHT:
				SHEET 1 OF 1	

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF APW COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF APW COMPANY IS STRICTLY PROHIBITED.